

KONTEJNERŪ:

Standard-Container 20'

ISO Type Group

22 GP

ISO Size Type

22 G1

		Millimeter/mm	Foot/ft
Internal	Length	5895	19' 4 1/8"
	Width	2350	7' 8 1/2"
	Height	2392	7' 10 1/8"

Door Opening	Width	2340	7' 8 1/8 "
	Height	2292	7' 6 1/4 "

		Kilogram/kg	Lbs/Pound
Weigh	Max. Gross	30480	67200
	Tare	2250	4960
	Max. Payload	28230	62240

		Cubic meter/m3	Cubic foot/cu.ft
Capacity		33,2	1172



Standard-Container 40'

ISO Type Group

42 GP

ISO Size Type

42 G1

		Millimeter/mm	Foot/ft
Internal	Length	12029	39' 5 1/2"
	Width	2350	7' 8 1/2"
	Height	2392	7' 10 1/8"

Door Opening	Width	2340	7' 8 1/2"
	Height	2292	7' 6 1/4"

		Kilogram/kg	Lbs/Pound
Weigh	Max. Gross	30480	67200
	Tare	3780	8330



Max. Payload 26700 58870

Cubic meter/m3Cubic foot/cu.ft

Capacity 67,7 2390

Standard-Container 40' High-Cube

ISO Type Group

45 GP

ISO Size Type

45 G1

Millimeter/mm Foot/ft

Internal	Length	12024	39' 5 3/8"
	Width	2350	7' 8 1/2"
	Height	2697	8' 10 1/8"
Door Opening	Width	2338	7' 8"
	Height	2585	8' 5 3/4"

Kilogram/kg Lbs/Pound

Weigh	Max. Gross	30480	67200
	Tare	4020	8860
	Max. Payload	26460	58340

Cubic meter/m3Cubic foot/cu.ft

Capacity 76,3 2694



Open-Top-Container 20'

ISO Type Group

20 UT

ISO Size Type

22 U1

		Millimeter/mm	Foot/ft
Internal	Length	5897	19' 4 1/8"
	Width	2350	7' 8 1/2"
	Height	2377	7' 9 1/2"
Door Opening	Width	2338	7' 8"
	Height	2280	7' 5 3/4"
Roof Opening	Width	2230	7' 3 3/4"
	Height	5439	17' 10 1/8"
		Kilogram/kg	Lbs/Pound
Weigh	Max. Gross	30480	67200
	Tare	4020	8860
	Max. Payload	26460	58340
		Cubic meter/m3	Cubic foot/cu.ft
Capacity		32,5	1149



Open-Top-Container 40'

ISO Type Group

40 UT

ISO Size Type

42 U1

		Millimeter/mm	Foot/ft
Internal	Length	12030	39' 5 5/8"
	Width	2350	7' 8 1/2"
	Height	2377	7' 9 1/2"
Door Opening	Width	2338	7' 8"
	Height	2292	7' 6 1/4"
Roof Opening	Width	2210	7' 3"
	Height	11573	37' 11 5/8"
		Kilogram/kg	Lbs/Pound
Weigh	Max. Gross	30480	67200



Tare	3850	8490
Max. Payload	26630	58708

Cubic meter/m³Cubic foot/cu.ft

Capacity	66,4	2345
----------	------	------

Flatrack-Container 20'

ISO Type Group

22 PC

ISO Size Type

22 P8

		Millimeter/mm	Foot/ft
Internal	Length floor	6038	19' 9 3/4"
	Length min.	5612	18' 4 7/8"
	Width floor	2438	8' 0"
	Width min.	2210	7' 2 7/8"
	Height	2213	7' 3 1/8"
	Height bottom	370	1' 2 9/16"
		Kilogram/kg	Lbs/Pound
Weight	Max. Gross	34000	74956
	Tare	2740	6040
	Max. Payload	31260	68910



Flatrack-Container 40'

ISO Type Group

42 PF

ISO Size Type

42 P1

	Millimeter/mm	Foot/ft	
Internal	Length floor	12086	39' 7 7/8"
	Length min.	11826	38' 9 5/8"
	Width floor	2224	7' 3 1/2"
	Width min.	2224	7' 3 1/2"
	Height	1981	6' 6"
	Height bottom	610	2'

	Kilogram/kg	Lbs/Pound	
Weight	Max. Gross	30480	67200
	Tare	4200	9265
	Max. Payload	26280	57935



Flatrack-Container 40' High-Cube

ISO Type Group

45 PC

ISO Size Type

45 P8

	Millimeter/mm	Foot/ft	
Internal	Length floor	12060	39' 6 3/4"
	Length min.	11660	38' 3 1/8"
	Width floor	2365	7' 9 1/8"
	Width min.	2200	7' 2 5/8"
	Height	2245	7' 4 3/8"
	Height bottom	648	2' 1 1/2"

	Kilogram/kg	Lbs/Pound	
Weight	Max. Gross	45000	99210
	Tare	5700	12570
	Max. Payload	39300	86640

